

DECK MORTAR

High Performance Readymix plaster based on premium quality riversand



Introduction

Deck Mortar ready mix cement plaster is a mix of premium quality graded river sand, high performance plasticizers and mineral binder. This cement plaster is specially designed for excellent strength, bonding and low rebound losses. Available in ready to use bags, it makes the application easy and fast. Deck Mortar eliminates the need for getting sand, cement and other additives and mixing them on the site. A high performance mix is assured as it is batched and blended in the stringent quality standards of the factory unlike mixing at sites.

Key features

- High quality, moisture and silt free river sand based plaster.
- Specially formulated for lower rebound losses and excellent bonding.
- High early strength development.
- No wastage at site.
- Easy to transport to higher floors.
- Enhanced productivity of plastering.

Technical Data

Form	Grey powder
Bulk density	1800 Kg/cu.m.
Compressive strength (7 days)	10 N/mm ²

Application Procedure

Surface Preparation

Surface should be clean and free of dust, grease etc. else it will affect the bonding of the plaster. If the surface is dry, it should be moistened with clean water.

Mixing

1. Prepare plaster mix by adding 6-7 liters of water per bag of Deck Mortar (50 kg). The correct ratio of water and Deck Mortar is essential for good plaster.

DECK MORTAR

High Performance Readymix plaster based on premium quality riversand

Application

1. Deck Mortar can be applied by hand as per standard practices in such a way that the single coat thickness does not exceed 15mm.
2. For faster application and better adhesion to the base, it is recommended to use the special plaster spray machine available. Please contact the manufacturer for details.

Packaging

50 kg bag

Storage

Deck Mortar must be stored in the original sealed packaging under cool and dry conditions. It must be protected from exposure to moisture or water. Shelf life is 6 months from the date of manufacturing.

Health and Safety

Kindly wear hand gloves and safety goggles while handling the product. Any contact with eyes should be washed immediately with clean water and medical advice should be sought. Do not swallow. Avoid contact with food or cooking utensils and keep away from children's reach.

Product Disclaimer

This product is manufactured with utmost care and precautions using best available materials, techniques and keeping in view the end use and assured performance. However, no specific guarantee can be given since the application of the product (prevailing site and environmental condition while applying etc.) is beyond our control. We therefore welcome consultation in the event of doubt about application performance.