

DECK SEALER

Wear Resistant Weather Stable Concrete Sealer

INTRODUCTION

Deck Sealer is a pure acrylic based low viscosity, transparent sealer for concrete surface. It is best suited for sealing concrete or stone surface where wear resistance is required while maintaining its aesthetic beauty. Deck Sealer is extremely resistant to hydrolysis and degradation due to sunlight thus provides a long lasting glossy finish to the surface.

KEY FEATURES

- Pure acrylic formulation ensures non yellowing coating
- Excellent adhesion with concrete, brick and natural stone
- Optimum viscosity and fast drying properties
- Resistant to hydrolysis
- Good wear resistance
- Transparent in colour and excellent gloss retention

TECHNICAL DATA

Dry to touch	Less than 1 hour
Recoat time	4-5 hours
Cure time	24 hours
Solid content	24% by weight
Coverage	5-6 sq.m./Kg/coat

APPLICATION PROCEDURE

- Make sure the surface is free from debris, de-shuttering oil, laitance, paint, grease etc. The moisture content in the concrete must be less than 5%.
- Remove dust using vacuum system or air blower.
- Take a clean and dry container of suitable size and take Deck Seal in it. Use Tin/ HDPE/ polycarbonate containers only. Do not use tinted PVC buckets or so as it will lead to colouration of Deck Sealer due to loss of colour from the tinted PVC container.
- Apply Deck Sealer on the prepared surface using clean brush/ roller. Allow it to dry for 1-2 hours before applying next coat. Make sure the brush

application direction for any two consecutive coats is perpendicular to each other.

PACKAGING

15 Kg in Can.

STORAGE

Store in the original container with the lid closed appropriately. Avoid extreme temperatures and direct exposure to sunlight. Keep in cool, dry and under shed. Deck Sealer performs well for at least 12 months from the date of manufacture if stored following aforesaid method.

HEALTH AND SAFETY

Kindly wear hand gloves and safety goggles while handling the product. Any contact with eyes should be washed immediately with clean water and seek medical advice. Do not swallow, avoid contact with food or cooking utensils and keep away from children's reach. If splashed on to cloth or any other fabric, wash immediately otherwise it may leave permanent stain.

PRODUCT DISCLAIMER

This product is manufactured with utmost care and precautions using best available materials, techniques and keeping in view the end use and assured performance. However, no specific guarantee can be given since the application of the product (prevailing site and environmental conditions while applying etc.) is beyond our control. We therefore welcome consultation in the event of doubt about application performance.